



XT3 Type III Multi-Purpose Dump Body

Hi-Way XT3 Type III Rear Discharge Multi-Purpose Dump Body

1. Spreads- Broadcast deicing materials at rear.
2. Hauls- Flat dump body floor allows hauling of virtually anything, including pallets and barrels.
3. Dumps- Front telescopic hoist provides low center of gravity.

Low Maintenance Features

- Heavy-duty 7-gauge 409 stainless steel inner and outer longitudinal sills are fully welded to body floor to resist corrosion and improve strength.
- 7-gauge grade 50 body sides feature one-piece construction with radius design to reduce material build-up. Sloped top rails on side sheets and headsheet add body support and prevent debris build-up on the rails.
- 3/16" (.48cm) AR400 conveyor floor resists bending from load impact and provides superior wear resistance.
- High torque 25:1 gear case starts even the heaviest loads. Includes idler with shafts, sprockets and bearing that remove as one assembly to simplify maintenance. Dropped forged steel sprockets ensure longer life.

High Productivity Features

- Quick detach front and/or rear spinner assemblies adjust up/down, side to side, and fore/aft for precise spread pattern control.

Optional Equipment

- Unpainted 201 or 304 stainless steel construction for added resistance to corrosion.
- Tool boxes, stainless underbody pan, pre-wet system, screens, ladder, and conveyor cover are some of the other options available.

HI-WAY XT3 Type III

XT3 Type III						
Length (ft)	Length (m)	Width	CA/CT*	Struck Capacity	Struck Capacity w/ Sideboards	Approx. Body Weight
10'	3.05	95.5" (243 cm)	84" (213 cm)	7.6 yds ³ (5.81 m ³)	11.2 yds ³ (8.56 m ³)	4323 lbs. (1961 kg)
11'	3.35	95.5" (243 cm)	96" (244 cm)	8.4 yds ³ (6.42 m ³)	12.4 yds ³ (9.48 m ³)	4513 lbs. (2047 kg)
12'	3.66	95.5" (243 cm)	108" (274 cm)	9.2 yds ³ (7.03 m ³)	13.6 yds ³ (10.40 m ³)	4703 lbs. (2133 kg)
13'	3.96	95.5" (243 cm)	108" (274 cm)	10.0 yds ³ (7.65 m ³)	14.7 yds ³ (11.24 m ³)	4893 lbs. (2219 kg)
14'	4.27	95.5" (243 cm)	120" (305 cm)	10.9 yds ³ (8.33 m ³)	16.0 yds ³ (12.23 m ³)	5083 lbs. (2306 kg)
15'	4.57	95.5" (243 cm)	132" (335 cm)	11.7 yds ³ (8.95 m ³)	17.1 yds ³ (13.07 m ³)	5273 lbs. (2392 kg)

*The Cab to Axle/Tandem dimensions are only guidelines. Consult federal, state and local weight laws and chassis manufacturer's ratings to ensure neither government weight restrictions, nor GVWR and GAWRs are exceeded.



Pre-Wet System

Liquid is blended into material prior to discharge onto the spinner through chain conveyor system.



Spinner

The rear spinner assembly adjusts up/down, side-to-side, and fore/aft for precise spread pattern control.



Hoist

Front telescopic hoist provides lower center of gravity when dumping. Cylinder includes 2-year warranty.



Body

95.5" (243cm) wide body provides maximum capacity. Body side sheets and floor feature one-piece construction.

Products and specifications subject to change without notice.
 Photos and illustrations may or may not include optional equipment.
 Hi-Way® is a registered trademark of Highway Equipment Company, Inc., d/b/a New Leader Manufacturing.
 © 2019 Highway Equipment Company, Inc., d/b/a New Leader Manufacturing.
 HWXT3-III-2019-01