



# XT3 Type II Multi-Purpose Dump Body

## Hi-Way XT3 Type II Front Discharge Multi-Purpose Dump Body

1. Spreads - Broadcast deicing materials in front of the drive tires for better traction and safety.
2. Hauls - Flat dump body floor allows hauling of virtually anything, including pallets and barrels.
3. Dumps - Front telescopic hoist provides low center of gravity.

### High Productivity Features

- Heavy-duty 7-gauge 409 stainless steel inner and outer longitudinal sills are fully welded to the body floor to resist corrosion and improve strength.
- 7-gauge grade 50 body sides feature "one piece" construction with radius design to reduce material build-up. Sloped top rails on side sheets and headsheets add body support and prevent debris build-up on rails.
- 3/16" (.48cm) AR400 conveyor floor resists bending from load impact and provides superior wear resistance.
- Sloped tailgate allows for added capacity, providing increased closing pressure and eliminating the need for an asphalt lip which can interfere with intake hoppers on paving or chipping equipment.
- 16.9" (43cm) wide cross conveyor handles larger capacity than auger feed or chute-style front discharge units.
- Quick detach front spinner assembly adjusts up/down, side-to-side, and fore/aft for precise spread pattern control.

### Available Options

- High volume liquid storage for pre-wet or anti-icing
- Unpainted 201 or 304 stainless steel construction for added resistance to corrosion.
- Tool boxes, stainless underbody pan, pre-wet system, screens, ladder, and conveyor cover are just some of the other options available.

# HI-WAY XT3 Type II


XT3 Type II						
Length (ft)	Length (m)	Width	CA/CT*	Struck Capacity	Struck Capacity w/ Sideboards	Approx. Body Weight
9'/10'	2.74/3.05	95.5"	84"	6.7 yds3	10.0 yds3	3998 lbs. (1813 kg)
10'/11'	3.05/3.35	95.5"	96"	7.5 yds3	11.1 yds3	4188 lbs. (1900 kg)
11'/12'	3.5/3.66	95.5"	108"	8.4 yds3	12.4 yds3	4378 lbs. (1986 kg)
12'/13'	3.66/3.96	95.5"	108"	9.2 yds3	13.6 yds3	4568 lbs. (2072 kg)
13'/14'	3.96/4.27	95.5"	120"	10.0 yds3	14.8 yds3	4758 lbs. (2158 kg)
14'/15'	4.27/4.57	95.5"	132"	10.8 yds3	15.9 yds3	4948 lbs. (2244 kg)

\*The Cab to Axle/Tandem dimensions are only guidelines. Consult federal, state and local weight laws and chassis manufacturer's ratings to ensure neither government weight restrictions, nor GVWR and GAWRs are exceeded.



## Spinner / Conveyor

The rear spinner assembly adjusts up/down, side to side, and fore/aft for precise spread pattern control.



## Hoist

Front telescopic hoist provides lower center of gravity when dumping. Cylinder includes 2-year warranty.



## Body

95.5" (243cm) wide body provides maximum capacity. Body side sheet and floor feature one-piece construction.



## Optional SB3 Sandbag Filler Attachment

- Constructed of 304 stainless steel and retrofits onto any existing XT3 Type I or III with rear discharge set-up.
- Capable of filling two 50-pound sandbags in 10 seconds.
- Offers quick and easy installation and removal.
- Features an adjustable vertical chute to accommodate varying truck heights and bag sizes as well as an adjustable 12-volt DC vibrator, which can be turned on and off with an optional control, to aid in the flow of sand through the chute.

Products and specifications subject to change without notice.  
Photos and illustrations may or may not include optional equipment.  
Hi-Way® is a registered trademark of Highway Equipment Company, Inc., d/b/a New Leader Manufacturing.  
© 2019 Highway Equipment Company, Inc., d/b/a New Leader Manufacturing.  
XT3II\_F&B