



# DS30

## Dry Nutrient Spinner Spreader

New Leader is the exclusive partner of John Deere® spinner spreaders. The DS30 is factory installed on the 600R chassis. The John Deere 612R or 616R liquid sprayers can also be configured as a combo machine with the DS30 dry spinner spreader.

### STANDARD FEATURES

- Variable rate technology (VRT) ranging from 75 lbs per acre to 3 tons per acre
- Removeable bolted-in rear endgate
- Pressurized chain oiler
- #4 belt-over-chain conveyor

### PATENTED PRECISION APPLICATION

Spread materials faster, wider, and more consistently, even on windy days, with proven G4 variable rate technology.



### CONTROLS

The John Deere 4600 CommandCenter and SpreadStar controller allows integrated control between the chassis and DS30.

# DS30 Specifications



## SINGLE BIN

The single bin is available in 304 stainless steel or 409 painted stainless steel. A removable end gate, inverted V, and electric oiler are included.

Unit Length	Estimated Weight	Struck Capacity
11 FT (3.35 M)	3,700 LBS (1,696 KG)	300 CU FT (8.50 CU M)

## MULTAPPLIER™

The MultApplier™ allows for two separate materials to be spread simultaneously and features a 24-inch wide #4 belt-over-chain conveyor. The direct-driven conveyor is also controlled independently enabling the delivery of material at variable rates through the adjustable gate at the rear of the hopper body. The hillside divider improves material placement on the spinner for a more effective spread pattern.



### Struck Capacity

Bin 1	MultApplier Bin	Total
162 CU FT (4.59 CU M)	106 CU FT (3.00 CU M)	268 CU FT (7.59 CU M)

Products and specifications subject to change without notice.  
Photos and illustrations may or may not include optional equipment.  
John Deere and the John Deere green and yellow trade dress are the trademarks of Deere & Company.