


DS20 G4



 1330 76th Ave SW
Cedar Rapids, Iowa

 319.363.8281

 NewLeader.com

DS20 G4

New Leader is the exclusive partner of John Deere spinner spreaders. The DS20 is factory installed on the 400R or 600R chassis.

Available in painted 409 stainless steel or unpainted 304 stainless steel, the DS20 G4 features the revolutionary G4 variable rate technology proven to spread materials faster, wider, and more accurately than before.

WHAT IT DOES

Standard Features

- 96-in (244cm) body width
- 11 ft (3.34m) body length
- 200 cu. ft (5.66m³) struck capacity
- Removable bolted-in rear endgate
- Pressurized chain oiler
- #4 belt-over-chain for combination fertilizer and lime applications
- A 30-inch-wide heavy-duty conveyor

Precision Application

Spread materials faster, wider and more consistently, even on windy days, with proven G4 variable rate broadcasting technology.

Add a MultiApplier for dual product application.

TECHNICAL DATA SHEET

Single Bin



DS20 G4	
Length	In (cm)
11' (4.27m)	132 (335)
Struck Capacity	Cu Ft (Cu M)
11' (3.34m)	200 (5.66)
Estimated Weight	Lbs (kg)
11' (3.34m)	3,640 (1,650)

MultApplier



MultApplier	5ft MultApplier
Est. Ship Weight	950 lbs (431kg)
	Capacities with 5ft MultApplier Cu Ft (Cu M)
Bin 1 Struck Capacity	106 (3.00)
Bin 2 Insert Capacity	66 (1.87)
Total Struck Capacity	172 (4.87)

MultApplier-Ready for Dual Product Application

The DS20 G4 can be easily converted to broadcast multiple products. Designed with a bolted-in endgate and stainless-steel hydraulic connections, this optional component can be added or removed with minimal effort. The dual hopper system features two independent conveyors that can simultaneously apply two products at predetermined or variable rates.