

DS30 G4



1330 76th Ave SW
Cedar Rapids, Iowa

319.363.8281

NewLeader.com



DS30 G4

New Leader is the exclusive partner of John Deere spinner spreaders. The DS30 is factory installed on the 600R chassis.

Available in painted 409 stainless steel or unpainted 304 stainless steel, the DS30 G4 features the revolutionary G4 variable rate technology proven to spread materials faster, wider, and more accurately than before.

WHAT IT DOES

Benefits

- 120 in. (305cm) body width
- 11 ft (3.34m) body length
- 300 cu.ft (8.5 m³) struck capacity
- Hold up to 10 tons (9,072 kg) of product
- Removable bolted-in rear endgate
- Pressurized chain oiler
- #4 belt-over-chain for fertilizer applications
- A 30-inch-wide heavy-duty conveyor

Precision Application

Spread materials faster, wider and more consistently, even on windy days, with proven G4 variable rate broadcasting technology.

Add a Multiplier for dual product application.

TECHNICAL DATA SHEET

Single Bin



DS30 G4	
Length	In (cm)
11' (3.34m)	132 (335)
Struck Capacity	Cu Ft (Cu M)
11' (3.34m)	300 (8.50)
Estimated Weight	Lbs (kg)
11' (3.34m)	3,740 (1,878)

MultApplier



MultApplier	5ft MultApplier
Est. Ship Weight	1,120 lbs (508kg)
	Capacities with 5ft MultApplier Cu Ft (Cu M)
Bin 1 Struck Capacity	162 (4.59)
Bin 2 Insert Capacity	106 (3.00)
Total Struck Capacity	268 (7.59)

MultApplier-Ready for Dual Product Application

MultApplier-ready, the DS30 G4 can be easily converted to broadcast multiple products. Designed with a bolted-in endgate and stainless-steel hydraulic connections, this optional component can be added or removed with minimal effort. The dual hopper system features two independent conveyors that can simultaneously apply two products at predetermined or variable rates.