

WHAT IT DOES

Precision Application

- Extra wide 34" (86cm) conveyor and 50 side slopes for better material flow and increased output
- Precise independent spinner control and monitoring

Ease of Use

- Hydraulic oil cooler
- Hydraulically-controlled feedgate for in-cab adjustments
- ISOBUS-ready

Ease of Maintenance

• Stainless steel conveyor floor

L5034

G4

More profit for less time in the field is possible with the L5034 G4 compost spreader. Built for durability and versatility, it gives operators the power to cover more ground faster, while maintaining an accurate spread pattern.

Spread up to 300 tons per day with spread widths up to 55' wide.

TECHNICAL DATA SHEET

L5034					
Unit Length (m)	Overall Length	Body Length	Frame Length	Outside Width	
13' (3.96m)	196" (497.8cm)	144" (366cm)	147" (373.4cm)	118" (299.7cm)	
14' (4.27m)	208" (528.3cm)	156" (396cm)	159" (403.9cm)	118" (299.7cm)	
16' (4.88m)	232" (589.3cm)	180" (457cm)	183" (464.8cm)	118" (299.7cm)	
18' (5.49m)	256" (650.2cm)	204" (518cm)	207" (525.8cm)	118" (299.7cm)	
21' (6.40m)	292" (741.7cm)	240" (610cm)	243" (617.2cm)	118" (299.7cm)	

L5034					
Unit Length (m)	Spreader Height	Struck Capacity Cu Ft (Cu M)	Approx. Weight lbs (kg)		
13' (3.96m)	70.7" (190cm)	361 (10.2)	5200 (2358)		
14' (4.27m)	70.7" (190cm)	392 (11.1)	5600 (2540)		
16' (4.88m)	70.7" (190cm)	453 (12.8)	6400 (2903)		
18' (5.49m)	70.7" (190cm)	515 (14.5)	7200 (3266)		
21' (6.40m)	70.7" (190cm)	608 (17.2)	8400 (3810)		





