



- 1330 76th Ave SW Cedar Rapids, Iowa
- 319.363.8281
- NewLeader.com

WHAT IT DOES

Productivity

- 120' spread pattern
- 33% more efficient high output design
- · Uniformity of spread pattern
- 16-section swath width
- Boundary and half-width spreading

Ease of Use

- Built-in spread pattern wizard
- Ability to pattern test and set the machine, using only 3 pans
- Ease of calibration
- Conveyor calibration is not required

Versatility

- Dual bins for two product application
- Low sensitivity to driving centers
- Variable rate width spreading from 120', 90', 80' and 70'

Ease of Maintenance

- Zero grease points
- New positive drive belt requiring minimal maintenance
- Tool-free components
- Easy to replace SS fin overlays

NL720

With dual bins and stacked conveyors, the NL720 represents a shift in the agriculture industry.

Combining unprecedented design with ease-of-use, the NL720 can help you achieve unrivaled productivity. Crop damage, unnecessary passes, overlap, and soil compaction will become a thing of the past for you and your business.

TECHNICAL DATA SHEET

NL720	
Length	In (cm)
12' (3.66m)	"A" 199 (505)
12' (3.66m)	"B" 138 (351)
12' (3.66m)	"C" 68 (173)
14' (4.27m)	"A" 223 (567)
14' (4.27m)	"B" 162 (411)
14' (4.27m)	"C" 68 (173)
Struck Capacity	Cu Ft (Cu M)
12' (3.66m)	303 (8.58)
14' (4.27m)	363 (10.28)
Est. Weight	Lbs (kg)
12' (3.66m)	6,085 (2,760)
14' (3.66m)	7096 (3,219)





