



**Tailgate Spreader**



# Tailgate Spreader

## Salt, Sand, and Gravel

Hi-Way Equipment features a range of road maintenance equipment aiming to bring quality, durability, and efficiency to your projects. From precise material application to robust construction needs, Hi-Way Equipment enhances road safety processes and sets the standard for unmatched performance in the industry.



SA-6C

### SA-6C

#### Salt, Sand

The SA-6C tailgate spreader features a heavy-duty 6" (15.2cm) bi-directional flighting ensuring material feeds evenly from both sides of the dump body to the left-hand discharge areas. Easy-open hinged bottom panel provides for quick clean out of trough and the quick-disconnect hardware enables easy removal or installation.

### Features

- Anti-flow plate is provided, over the discharge opening, to prevent loss of materials.
- Direct drive hydraulic motor eliminates chain and sprocket or gear case maintenance.
- Quick disconnect mounting kit enables fast removal and mounting of spreader without the use of specialized tools.





## SA-9

### *Aggregates, Gravel, Salt, Sand*

The SA-9 tailgate spreader is designed for year-round road maintenance. For road maintenance during the winter months, the auger conveys material to the left and is dispersed through a spinner, spreading material from 4' to 40' in width. For the non-winter months the auger can be reversed, providing material discharge to the right for berming, patching, or trench filling operations.

- Heavy-duty 7-gauge cover / back plate and trough assembly with 1/4" endplates.
- Easy-open hinged bottom panel provides for quick clean out of trough and the quick-disconnect hardware enables easy removal or installation.
- 9" diameter auger with 5/8" thick helicoid flighting is welded to a heavy-duty 2-1/2" schedule 80 pipe.
- 8" polyurethane spinner disc with six fins provides a uniform spread pattern from 4 to 40 feet wide. The spinner assembly can be easily removed without the need for tools and can be easily adjusted to vary the spread pattern maintenance.

## TGC-18

### *Aggregates, Sand*

The TGC-18 tailgate spreader attachment is designed to be used for road shoulder berming, back filling trenches, pothole repair and conveying both hot and cold asphalt. When equipped with the optional spinner attachment, the TGC-18 becomes a unit capable of spreading salt and sand for deicing or spreading aggregates for chip-sealing projects.

- Both endgates adjust for controlled material flow and swing open for high-speed dumping.
- Quick disconnect mounting kit enables fast mounting and removal of spreader without the use of tools.
- 18" (46cm) wide belt-over-chain conveyor riveted to 1/4" x 1" (6mm x 25mm) cross bars for either right- or left-hand discharge.





# Tailgate Spreader Specifications

Compare and contrast Hi-Ways portfolio of Tailgate Spreaders.

## SA-6C

Height w/ Spinner	Height w/o Spinner	Depth w/ Spinner	Depth w/o Spinner	Width	Shipping Weight Approx.
33.5" (85 cm)	19.125" (49 cm)	21.125" (54 cm)	18" (46 cm)	96" (244 cm)	550 lbs. (250 kg)

## SA-9

Height w/ Spinner	Height w/o Spinner	Depth w/ Spinner	Depth w/o Spinner	Width	Shipping Weight Approx.
39.187" (99 cm)	26.187" (67 cm)	27.312" (69 cm)	24.875" (67 cm)	99.562" (253 cm)	900 lbs. (408.2 kg)

## TGC-18

Height w/ Spinner	Height w/o Spinner	Depth	Width w/ Spinner	Width	Shipping Weight Approx.
34.5" (88 cm)	24.5" (62 cm)	42.5" (108 cm)	108" (259 cm)	102" (274 cm)	750 lbs. (340.2 kg)

Products and specifications subject to change without notice.  
Photos and illustrations may or may not include optional equipment.  
Hi-Way® is a registered trademark of Highway Equipment Company, Inc., d/b/a New Leader Manufacturing.  
© 2025 Highway Equipment Company, Inc., d/b/a New Leader Manufacturing.



Manufactured by

**NEW LEADER MANUFACTURING**

1330 76th Avenue SW | Cedar Rapids, Iowa 52404

[information@newleader.com](mailto:information@newleader.com)

[www.newleader.com](http://www.newleader.com)

Ph. 800.363.8281